

WATER PRESSURE TRANSMITTER VPL 16

Water pressure transmitter VPL 16 is designed to detect pressures at the HVAC automation systems. The pressure is measured with ceramic sensor element. Allowed mediums are water, water/glycol mixtures, air and oils.

Output is directly proportional to the pressure inside the pipeline. Material of wetted parts is stainless steel (AISI 303) and housing for electrical connections is made of heat resisting plastics.

When the transmitter is connected to the cold / chilled water circuit, condensation on the sensor must be prevented. The condensation can be prevented by installing the transmitter far enough from the cold pipe, for example.

The range for measuring can be chosen at commissioning. The cover with display can be added afterwards. The socket for display is ready installed on the card.

ATTENTION!


Device may be damaged by overpressure if installation is made against fluid and closed valve.


IMPORTANT: If the red indicator light turns on, the device is defective and must be replaced.

Measuring range selection:

S1	S2	Range (bar)
••	••	02,5
	••	06
• •		010
		016

Wiring







Technical data:

Supply 24 Vac/dc, 1 VA
Ranges 0...2,5 bar
0...6,0 bar
0...10 bar
0...16 bar

Mounting R ½"

Outputs 0...10 Vdc, < 2 mA 4...20 mA, < 800Ω

Inaccuracy < 0,1 bar

Temperature drifting $< \pm (0.04 \text{ bar} + 0.2 \% \text{ of span}) / 10 \text{ K}$

Long term stability < 0,2 bar / year

Operating conditions

humidity non-condensing temperature 0...+60 °C
Allowed medium temp. 0...+85 °C
Max. overpressure 50 bar
Max. negative pressure 1 bar

Protection class IP54, cable gland or sensor down

27 mm

Materials

Tool

wetting parts AISI 303 (stainless) housing heat resisting plastic

Ordering guide:

Model Product Description

VPL 16 1134050 water pressure transmitter ranges 0-2.5, 0-6, 0-10 or 0-16 bar VPL 16-N 1134051 water pressure transmitter with

display

Products fulfil the requirements of directive 2014/30/EU and are in accordance with the standards EN61000-6-3 (Emission) and EN61000-6-2 (Immunity).